# **Material Safety Data Sheet**



# 1. Product and company identification

Product name	Castrol Transynd Allison Transmission Fluid
MSDS #	464296
Code	464296-US65
Product use	Transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION:	1 (800) 447-8735
	Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

### 2. Hazards identification

Physical state	Liquid.		
Color	Red.		
Emergency overview	CAUTION !		
	MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.		
	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.		
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.		
Potential health effects			
Eyes	May cause eye irritation.		
Skin	May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.		
Inhalation	May cause respiratory tract irritation.		
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.		
See toxicological information (Section 11)			

Product name Castrol Tr	ansynd Allison Transmission Fluid		Product code	464296-US65	Page: 1/6
Version 1 Date of is	ssue 02/15/2011.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

## 3. Composition/information on ingredients

Synthetic base stock. Proprietary performance additives.

Ingredient name CAS # %	
Base oil - highly refinedVaries5 - 10	

### 4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

### 5. Fire-fighting measures

Flash point	Open cup: >235°C (>455°F) [Cleveland.]		
Fire/explosion hazards	In a fire or if heated, a pressure increase will occur and the container may burst.		
Extinguishing media			
Suitable	Use an extinguishing agent suitable for the surrounding fire.		
Not suitable	Do not use water jet.		
Fire-fighting procedures	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.		
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide)		
Protective clothing (fire)	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.		

### 6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water- soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product name	Castrol Transyr	nd Allison Transmission Fluid		Product code	464296-US65	Page: 2/6
Version 1	Date of issue	02/15/2011.	Format	US	Language	ENGLISH
				(US)		(ENGLISH)

### 7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 8. Exposure controls/personal protection

Occupational exposure limits	5
Ingredient name	Occupational exposure limits
Base oil - highly refined	ACGIH (United States). TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Mineral oil, mist OSHA (United States). TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Mineral oil, mist
	components may be shown in this section, other components may be present in any mist, vapor or specific OELs may not be applicable to the product as a whole and are provided for guidance only.
Some states may enforce mo	ore stringent exposure limits.
<b>Control Measures</b> Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or use process enclosures, local exhaust ventilation or other engineering controls to keep w exposure to airborne contaminants below any recommended or statutory limits.	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
Personal protection	
Eyes	Avoid contact with eyes. Safety glasses with side shields or chemical goggles.
Skin and body	Avoid contact with skin and clothing. Wear suitable protective clothing.
<b>Respiratory</b> Use adequate ventilation. In accordance with good industrial hygiene and safety work practicable airborne exposures should be controlled to the lowest extent practicable.	
Hands	The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
	Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

### 9. Physical and chemical properties

Physical state	Liquid.
Color	Red.
Flash point	Open cup: >235°C (>455°F) [Cleveland.]
Specific gravity	0.8482
Viscosity	Kinematic: 38 mm²/s (38 cSt) at 40°C Kinematic: 7.4 mm²/s (7.4 cSt) at 100°C
Solubility	insoluble in water.

Product name	Castrol Transyr	d Allison Transmission Fluid		Product code	464296-US65	Page: 3/6
Version 1	Date of issue	02/15/2011.	Format	US	Language	ENGLISH
				(US)		(ENGLISH)

### 10. Stability and reactivity

Stability and reactivity	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

### 11. Toxicological information

#### Other information

Potential chronic health effects

Carcinogenicity

No known significant effects or critical hazards.

### 12. Ecological information

#### Ecotoxicity

No testing has been performed by the manufacturer.

### 13. Disposal considerations

#### Waste information

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

### 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

### 15. Regulatory information

#### U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: No products were found. SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol Transynd Allison Transmission Fluid: Immediate (acute) health hazard

#### **SARA 313**

Product name Castrol Transynd Allison Transmission Fluid				Product code	464296-US65	Page: 4/6
Version 1	Date of issue	02/15/2011.	Format	US	Language	ENGLISH
				(US)		(ENGLISH)

Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):	CERCLA: Hazardous substances.: Ethyl acrylate: 1000 lbs. (454 kg); Phenol: 1000 lbs. (454 kg);
State regulations	
Massachusetts Substances	None of the components are listed.
New Jersey Hazardous Substances	None of the components are listed.
Pennsylvania RTK Hazardous Substances	None of the components are listed.
California Prop. 65	<b>WARNING:</b> This product contains a chemical known to the State of California to cause cancer. Ethyl acrylate
Other regulations	
Canada inventory	All components are listed or exempted.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.
Australia inventory (AICS)	All components are listed or exempted.
China inventory (IECSC)	At least one component is not listed.
Japan inventory (ENCS)	Not determined.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	Not determined.

### 16. Other information

Label requirements	CAUTION !					
	MAY CAUSE R	RESPIRATORY	TRACT, EYE AND SKIN I	RRITATION.		
HMIS® Rating :	Health Flammability Physical Hazard Personal protection	1 1 0 X	National Fire Protection Association (U.S.A.)	Health Health Fire hazard Health Specific hazard		
History						
Date of issue	02/15/2011.					
Date of previous issue	No previous va	lidation.				
Prepared by	Product Stewar	rdship				
Notice to reader						

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the

Product name Castrol Transynd Allison Transmission Fluid				Product code	464296-US65	Page: 5/6
Version 1	Date of issue	02/15/2011.	Format	US	Language	ENGLISH
				(US)		(ENGLISH)

product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Ī	Product name Castrol Transynd Allison Transmission Fluid					Product code	464296-US65	Page: 6/6
	Version 1	1	Date of issue	02/15/2011.	Format	US	Language	ENGLISH
						(US)		(ENGLISH)