

SAFETY DATA SHEET



WRENCH

DATE PRINTED	7/1/2015
SDS REF. No:	LG-8066

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name: WRENCH

Product Identification: LG-8066

Synonyms: Blend of Petroleum Distalites

Product Use Description: Blend of Petroleum Distalites

General Info Phone: (972) 247-7111

Emergency Phone: (800) 535-5053

Supplier:

ARROW/MAGNOLIA

P.O. BOX 59089

DALLAS, TX 75229

2. HAZARDS IDENTIFICATION

CLASSIFICATION:

Aspiration Hazard - Category 1

Skin Irritation - Category 2

Eye Irritation - Category 2

Specific Target Organ Toxicity (single exposure) - Category 3

Flammable Aerosols - Category 1

Gasses under Pressure - Liquefied gas



Irritant

Flammable

Compressed Gas

Health Hazard

SIGNAL WORD: Danger

HAZARD STATEMENTS:

Keep out of reach of children.

Read label and SDS before use.

Extremely flammable aerosol.

Contains gas under pressure, may explode if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

PRECAUTIONARY STATEMENTS:

PREVENTION

Avoid breathing mist/spray.

Use only outdoors in well-ventilated area.

Keep away from heat, sparks, open flames and hot surfaces. No Smoking.

Do not spray on an open flame or other ignition source.

Pressurized container. Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

SAFETY DATA SHEET

WRENCH

Wear protective gloves.

Wear eye protection.

Response

IF SWALLOWED: Immediately call a poison center or a doctor. DO NOT induce vomiting,

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists. Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call poison center or doctor if you feel unwell.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50 C/122 F.

Store in well-ventilated place.

Store locked up.

Disposal

Disposal of contents and container in accordance with all local, regional and national regulations.

Hazards: Not applicable.

3. COMPOSITION

Chemical Name	CAS #	Concentration % by Weight
Severely Hydrotreated Naphthenic Petroleum Oil	64742-52-5	$\geq 50 \leq 70$
Distillates (petroleum), hydrotreated light	64742-47-8	$\geq 5 \leq 10$
Isobutane	75-28-5	$\geq 15 \leq 20$
Lubricant Base Oil	N/A	$\geq 10 \leq 15$
Propane	74-98-6	$\geq 1 \leq 5$

4. FIRST AID MEASURES

EMERGENCY OVERVIEW

DANGER: Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

5. FIREFIGHTING MEASURES

Suitable fire extinguishing media: Use water spray, fog or foam.

Specific hazards arising from the chemical:

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Bursting aerosol containers may be propelled from a fire at high speed. Gas may accumulate in confined areas and displace oxygen causing suffocation.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide.

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode

SAFETY DATA SHEET

WRENCH

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Put on appropriate personal protective equipment. (see Section B)

Environmental Precautions and Clean-Up Methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Eliminate all ignition sources.

Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7. HANDLING AND STORAGE

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting.

Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing.

Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal.

Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Distillates (petroleum), hydrotreated light

ACGIH TLV

200 mg/m³

Propane

ACGIH TLV

1000 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value		
Appearance	CLEAR SPRAY/MIST	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	-26.5 C	Color	COLORLESS
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	105 F (liquid portion)	Melting/Freezing Point	-NOT AVAILABLE
Odor	SOLVENT	Odor Threshold	NOT AVAILABLE
Other Information	VOC content(wt. %):28	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID
Relative Density	0.8	Solubility (Water)	INSOLUBLE
Vapor Density	NOT AVAILABLE	Vapor Pressure	592 kPa absolute @ 70
Viscosity	NOT AVAILABLE	pH	NOT APPLICABLE

SAFETY DATA SHEET

WRENCH

10. STABILITY AND REACTIVITY

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability: Stable under normal conditions.

Incompatible Materials: Acids and strong oxidizers

Conditions to Avoid: High temperatures, open flames, sparks, welding.

Decomposition Products: CO, CO₂

Vapors may ignite at temperatures exceeding flash point.

11. TOXICOLOGY INFORMATION

Primary Route of Entry: Inhalation, skin contact

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system.

Reproductive/Developmental Information: None known.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP, or OSHA.

Acute Toxicity Values:
Not available

SAFETY DATA SHEET

WRENCH

12. ECOLOGICAL INFORMATION

Not Available..

13. DISPOSAL CONSIDERATIONS

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

14. TRANSPORT INFORMATION

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number	1950
Proper shipping name	Aerosols, nonflammable
Class	2.1
Packing group	

15. REGULATORY INFORMATION

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under **California Proposition 65** (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed or this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

d001

SAFETY DATA SHEET

WRENCH

16. OTHER INFORMATION

HMIS Ratings :

HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	G

Disclaimer: This manufacturer believes that the information contained in the Safety Data Sheets is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also the suggestions should not be confused with, nor followed in violation of applicable law, regulations, rules or insurance requirements.

Preparation Revision Date: 5/30/15