Printing date 01/04/2021 Revised On 01/04/2021

1 Identification of the substance and manufacturer

Trade name: **GLOSS WHITE** 0000011413 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor. Eye Irrit. 2A H319 Causes serious eye irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms







Signal word

Warning

Hazard statements Flammable liquid and vapor. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. **Precautionary statements**

Keep container tightly closed.
Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO2, powder or water spray.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
64742-47-	Mineral Spirits	15-25%
13463-67-	7 titanium dioxide	≥15-<20%
7727-43-	7 barium sulfate	10-15%
1330-20-	7 xylene (mix)	1-5%

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water.

After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting

Most important symptoms and

effects: No further relevant information available.

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

No further relevant information available. Special hazards:

Protective equipment for firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Not required.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/04/2021 Revised On 01/04/2021

Trade name: GLOSS WHITE

Methods and material for

(Contd. of page 1)

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV (USA) Long-term value: 5* mg/m³

*inhalable fraction; E

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA)

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Wash hands after use. **Hygienic protection:** Do not eat or drink while working.

Breathing equipment: Not required.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

Eye protection:

9 Physical and chemical properties

Decomposition temperature:

Appearance: Liquid.

Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. 157 °C (314.6 °F) **Boiling point:** Flash point: 43 °C (109.4 °F) Flammability (solid, gas): Flammable.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Not determined.

Lower Explosion Limit: 0.5 Vol % **Upper Explosion Limit:** 6.5 Vol %

Vapor pressure: Not determined. Vapor density Not determined. **Evaporation rate** Not determined. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

10 Stability and reactivity

Conditions to avoid: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

Printing date 01/04/2021 Revised On 01/04/2021

Trade name: GLOSS WHITE

(Contd. of page 2)

11 Toxicological information

LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

LD50 >20,000 mg/kg (rat) Oral Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

1330-20-7 xylene (mix)

LD50 8,700 mg/kg (rat) Oral Dermal LD50 2,000 mg/kg (rbt) Inhalative LC50/4 h 6,350 mg/l (rat)

Information on toxicological effects: No data available. No irritant effect. Skin effects: Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

UN-Number

DOT UN1263 DOT Paint **1263 PAINT ADR**

Transport hazard class(es):

Class 3 Flammable liquids

Warning: Flammable liquids Special precautions for user:

F-E,S-È EMS Number: **Stowage Category**

Packaging Group: Ш

UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate 1330-20-7 xylene (mix)

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

7727-43-7 barium sulfate D, CBD(inh), NL(oral)

(Contd. on page 4)

Page 4/4

Safety Data Sheet

Printing date 01/04/2021

Trade name: GLOSS WHITE

(Contd. of page 3)

1330-20-7 | xylene (mix)

16 Other information

Contact: Regulatory Affairs